









TABLE 1

1	2	3	4	5	6	7	8	9	10
1	1	1	1	1	1	1	1	1	1

TABLE 2

1	2	3	4	5	6	7	8	9	10
1	1	1	1	1	1	1	1	1	1

REINFORCEMENT SCHEDULE

1. ALL REINFORCEMENT SHALL BE 12MM DIA. BARS UNLESS OTHERWISE SPECIFIED.

2. ALL BARS SHALL BE LAP JOINTED AT MIDSPAN OF SPAN.

3. ALL BARS SHALL BE DEVELOPED AS PER IS 456:2000.

4. ALL BARS SHALL BE PROTECTED BY 25MM CONCRETE COVER UNLESS OTHERWISE SPECIFIED.

5. ALL BARS SHALL BE PROTECTED BY 50MM CONCRETE COVER AT CORNERS AND EDGES.

6. ALL BARS SHALL BE PROTECTED BY 75MM CONCRETE COVER AT JOINTS.

7. ALL BARS SHALL BE PROTECTED BY 100MM CONCRETE COVER AT ENDS.

8. ALL BARS SHALL BE PROTECTED BY 125MM CONCRETE COVER AT CORNERS AND EDGES.

9. ALL BARS SHALL BE PROTECTED BY 150MM CONCRETE COVER AT JOINTS.

10. ALL BARS SHALL BE PROTECTED BY 175MM CONCRETE COVER AT ENDS.